


**5.0 A Single-Phase Silicon Bridge Rectifier**  
 Rectifier Reverse Voltage 50 to 1000V

**Features**

- This series is UL listed under the Recognized Component Index, file number E142814
- The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- Ideal for printed circuit board mounting
- High surge current capability
- High temperature soldering guaranteed 265°C /10 seconds at 5 lbs (2.3kg) tension



**Mechanical Data**

Case: Reliable low cost construction utilizing molded plastic technique

Terminals: Plated leads solderable per MIL-STD-202, Method 208

Mounting Position: Any

Weight: 0.92 ounce, 25.3 grams (approx)



Dimensions in millimeters(1mm = 0.0394")

**Maximum Ratings & Thermal Characteristics**

Rating at 25°C ambient temperature unless otherwise specified, Resistive or Inductive load, 60 Hz.  
 For Capacitive load derate current by 20%.

Parameter	Symbol	RS501	RS502	RS503	RS504	RS505	RS506	RS507	unit
Maximum repetitive peak reverse voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS bridge input voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	VDC	50	100	200	400	600	800	1000	V
Maximum average forward rectified output current at TA=50°C	IF(AV)				5.0				A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	IFSM				200				A
Rating for fusing ( t<8.3ms)	I <sup>2</sup> t				10				A <sup>2</sup> sec
Typical thermal resistance per element (1)	ReJA				50.0				°C / W
Typical junction capacitance per element (2)	C <sub>j</sub>				24				pF
Operating junction and storage temperature range	T <sub>j</sub> , T <sub>STG</sub>				-55 to + 150				°C

**Electrical Characteristics**

Rating at 25°C ambient temperature unless otherwise specified. Resistive or Inductive load, 60Hz.  
 For Capacitive load derate by 20 %.

Parameter	Symbol	RS501	RS502	RS503	RS504	RS505	RS506	RS507	Unit
Maximum instantaneous forward voltage drop per leg at 5.0A	VF				1.1				V
Maximum DC reverse current at rated TA =25°C DC blocking voltage per element TA =100°C	IR				10 500				μA


Notes: (1)Thermal resistance from Junction to Ambert on P.C.board mounting.

(2)Measured at 2.0MHz and applied reverse voltage of 4.0 volts.


**5.0 A Single-Phase Silicon Bridge Rectifier**  
Rectifier Reverse Voltage 50 to 1000V

**Rating and Characteristic Curves** (  $T_A = 25^\circ\text{C}$  Unless otherwise noted )  
**RS501 thru RS507**


**Fig. 1 Derating Curve for Output Rectified Current**




**Fig. 2 Maximum Non-repetitive Peak Forward Surge Current**



**Fig. 3 Typical Instantaneous Forward Characteristics**



**Fig. 4 Typical Reverse Characteristics**



**Fig. 5 Typical Junction Capacitance**

